



STANDARD LOADED VERSION

HQC41800S1S12C

SA D495ASC-45



Super Bearing Capacity



- Reinforced 50# fifth wheel
- High strength steel frame
- Reinforced front and rear suspension

High Reliability



- High load 300 double- reduce axle
- Double stage high efficiency desert air filter
- Special chassis protective armor

High comfort



- Super large driving space
- Deluxe leather seats
- Super quiet cabin

High Passing Ability



- Middle bumper
- Inter wheel differential lock
- Mixed pattern tyre

Model code		HQC41800S1S12C	
Bearing Type		Composite Transportation	
Basic Parameter	Drive mode	4×2	●
	Curb Weight (kg)	7.5	●
	GCW (t)	45	●
	Maximum Speed	110	●
Dimension	L×W×H(mm)	6465×2545×3935	●
	Wheelbase(mm)	4000	●
	Front Suspension/ Rear Suspension(mm)	1515/950	●
Cabin	High Roof Flat Floor and Double Sleeper		●
	Middle Bumper		●
	12-inch Central Control Screen		●
	Electric Heating Rear Mirror		●
	Flip Eagle Eye Headlamp		●
	Multi-Function Steering Wheel + Pneumatic Steering Column Adjustment		●
	Deluxe Leather Airbag Damping Seat		●
	850mm Wide Sleeper		●
	Four Point Spray Wiper		●
	Front Sun Visor + Left Side Sun Visor		●
	Color	SANY Red	
Pearl White		●	
Engine	Engine Model	D12C3-490E0	●
	Displacement	12.12L	●
	M Rated Power	490HP/360kW	●
	Maximum Torque (N.m)	2200	●
Transmission	Model	F12JZ-OD+QHG50B	●
	Ratio	Overdrive Gear 0.78	●
Front Axle	Model	7.5t	●
Rear Axle	Mode	13t	●
	Ratio	3.866	●
Brake	Mode	Front and Rear Drum Brakes + Super Wear-Resistant Friction Plates	●
Double Differential Lock	Mode	Inter-axle Differential Lock	/
		Inter-wheel Differential Lock	●
Fuel Tank	Capacity(L)	700+300	●
Wheel	Rim	Steel	●
	Tire	315/80R22.5	●
Suspension	Mode	Leaf Spring, Front 3, Rear 4+3	●
Other	Battery	220Ah	●
	Air Conditioner	Automatic Air Conditioner	●
	The Fifth Wheel	50#	●

Remarks:

- ① This configuration is only for reference, and the actual object shall prevail;
- ② Applicable scenario: This model is applicable to port containers, sand and coal transportation, etc;
- ③ Applicable road conditions: This model is suitable for medium and short distance transportation on paved roads such as high-speed, provincial and national roads.