

LP9018Ⅲ LINE PUMP

LP9018Ⅲ 车载泵

01 易损件寿命提升 & 可靠性提升
Durability & Reliability

02 提供易损件长期服务
Wear parts with long service life

03 低维护成本
Low maintenance cost

04 节能、低油耗
Energy conservation and
low fuel consumption

05 高效便捷
Efficiency and convenience

06 智能控制系统
Intelligent control system



TECHNICAL PARAMETER

技术参数

| 产品型号 Product Model | | LP9018 III | |
|---|---|--------------------------------|-----------------|
| 整车参数 Dimensions | 全长 Overall Length(mm) | 9360 | |
| | 总宽 Overall Width(mm) | 2500 | |
| | 总高 Overall Height(mm) | 3090 | |
| | 上料高度(H1) Feeding height | 1460 | |
| | 轴距(L1) Wheelbase | 4700 | |
| | 总重 Gross Weight(kg) | 12900 | |
| 泵送参数 Pumping Specifications | 混凝土理论输送压力 Max. Delivery Pressure (theoretical) | 低压 Low Pressure(MPa) | 9 |
| | | 高压 High Pressure(MPa) | 18 |
| | 混凝土理论输送量 Max. Concrete Output (theoretical) | 低压 Low Pressure(m³/h) | 100 |
| | | 高压 High Pressure(m³/h) | 55 |
| | 理论泵送次数 Pumping Times (theoretical) | 低压 Low Pressure(times/min) | 25 |
| | | 高压 High Pressure(times/min) | 14 |
| | 输送缸 Delivery cylinder | 缸径 Bore(mm) | 230 |
| | | 行程 Stroke(mm) | 1600 |
| | 料斗容积 Hopper Capacity(m³) | | 0.6 |
| | 发动机型号 Upper Engine Model | | D09S3-272E0 |
| 发动机额定功率/转速 Rated Power of Upper Engine(kW/rpm) | | 200/2200 | |
| 底盘参数 Chassis Specifications | 底盘品牌 Chassis Brand | | SANY |
| | 底盘型号 Chassis Model | | HQC1130 |
| | 最大允许总质量 Maximum Allowable Total Mass(kg) | | 13200 |
| | 发动机型号 Model of Engine | | ISDe180 30 |
| | 发动机功率 Engine Rated Power(kW/rpm) | | 132/2500 |
| | 发动机最大净功率 Engine Max Net Power(kW/rpm) | | 128/2500 |
| | 轮胎规格 Type Specifications | | 9.00R20 |
| | 排放标准 Emission Standard | | CHINA STAGE III |
| | 燃料箱容积 Fuel Tank Capacity(L) | | 300 |
| | 排量 Displacement(L) | | 4.5 |
| 最大速度 Max. Speed(km/h) | | 90 | |



SANY HEAVY INDUSTRY CO., LTD.

SANY Industry Town, Changsha Economic and Technological Development Zone,
Hunan Province, China

Service Line: +86 4006 098 318 E-mail: crd@sany.com.cn

SANY[®]
QUALITY CHANGES THE WORLD.