



SY206C-8Y(V) TRUCK MIXER



Distinct advantage in carrying capacity

Carrying capacity increased by 20%. Waterproof performance increased to 3-5 times by upgrading the seal structure of full set of axle.

Industry-leading mixing drum technology

Mixing drum using the customized SY300TP special purpose high strength and abrasion-resistant steel, drum service life extended by 30%, 8 years long service life. Lighter, more reliable, more economical and more valuable.

Self-developed integrated design

Upper parts and chassis integrated design take vehicle performance into account. Vehicle center of mass lowered 120mm by improve "no sub frame" structure matching with high strength frame. Driving is safer and more reliable.

Brand new driving experience

Upgraded air-floating adjustable seat, the sleeper berth is 130mm wider and 90mm thicker, and 95L storage space is set under the sleeper, which is more comfortable and spacious, and brings customers a brand-new driving experience.

Lightweight design

Aluminum alloy water tank is adopted, and the weight is reduced by 45%; The auxiliary chute is made by polymer, and the weight is reduced by 50%. Low-carbon, eco-friendly and more economical.

Technical specifications 技术参数

Model 型号		SY206C-8Y(V)	
Overall parameters 整车参数	Rudder direction	左右舵 左舵 Left	
	Curb weight (kg)	整备质量 (kg) 8000	
	Full load weight (kg)	最大允许总质量 (kg) 22400	
	Dimension (L × W × H) (mm)	整车尺寸 (长 × 宽 × 高) (mm) 7800 × 2480 × 3605	
	Wheel base (mm)	轴距 (mm) 4200	
	Min. ground clearance (mm)	最小离地间隙 (mm) ≥ 225	
	Min. turning diameter (m)	最小转弯直径 (m) ≤ 16	
	Fuel consumption (L/100km)	百公里油耗 (L/100km) ≤ 28	
	Braking distance (V ₀ =30km/h) (m)	制动距离 (V ₀ =30km/h) (m) ≤ 10(Full load); ≤ 9(Empty load)	
	Chassis 底盘配置	Engine	发动机 玉柴 Yuchai YC4EG200-50
Displacement (L)		排量 (L) 4.73	
Rated power/Rev speed (kW/rpm)		额定功率 / 转速 (kW/rpm) 147/2500	
Max. torque/Rev speed (N.m/rpm)		最大扭矩 / 转速 (N.m/rpm) 735/1300-1500	
Emission standard		排放标准 Euro V	
Gear-box		变速箱 法士特 Fast 8JS75F-C	
Front axle		前桥 5T	
Middle, rear axle		后桥 13T	
Cab		驾驶室 三环驾驶室 Sanhuan Cab	
Tyre		轮胎 12R22.5	
Brake type		制动型式 气压双回路鼓式制动 Pneumatic dual-circuit drum brake	
Fuel tank		燃油箱 (L) 170	
Drum 上装参数		Mixing capacity (m ³)	搅动容量 (m ³) 6
		Feeding speed (m ³ /min)	进料速度 (m ³ /min) ≥ 3
		Discharge speed (m ³ /min)	出料速度 (m ³ /min) ≥ 2
	Discharge residual rate	出料残余率 ≤ 0.5%	
	Slump scope (mm)	坍塌度范围 (mm) 50 - 210	
	Water tank capacity (L)	水箱容积 (L) 300	
	Water pressure (Mpa)	供水工作压力 (MPa) 0.35 - 0.38	
	Reduction gear	减速机 卓士博 TOP T60	
	Oil pump	油泵 三一 Sany 56	
	Motor	马达 三一 Sany 63	

Optional configuration 可选配置

Model 型号		SY206C-8Y(V)
Item 名称		● Standard 标配 ○ Option 选配 - None 无
Engine	发动机	-
Reduction gear	减速机	-
Mixing drum type	搅拌筒型式	-
Driving recorder	行车记录仪	-
Rootcloud	树根互联	○
Mixing drum forward and backward rotation sensor (GPS Terminal-EMEA must be installed)	搅拌筒正反转 (必须安装树根盒子)	●
Central control screen	中控屏	-
Embedded lock machine	预埋锁机	○
Blind zone radar	盲区雷达	-
Rear view camera	倒车摄像头	●
Around view monitor(AVM)	360 环视	-
ABS (axles need replacing)	ABS (需换车桥)	●
Cab roof warning light	驾驶室警示顶灯	-
Tyre	轮胎	-
Hydraulic lift of main chute	主槽液压举升	-
Multiple auxiliary chutes	多节副槽	-
Toolkit	工具箱	-
Rear working light	后照灯	●
Mixing drum cleaning device	搅拌筒清扫杆	-
Hopper components	接料斗	-
Special coating	特殊涂装	○
Water tank capacity	水箱容积	○ 400L 铝合金 Al
The upper guardrail protecting net of mixing drum	搅拌筒上部护栏保护筛网	-

SANY HEAVY INDUSTRY CO., LTD.

SANY Industrial Park, Economic and Technological Development Zone, Changsha, Hunan, China, 410100
Sales Hotline: 0086-731-85835199
Tel: 0086-731-85835199
Mail: sales@sanyglobal.com

Service Hotline: 4006098318
Tel: 0086-4006098318
Mail: CRD@sany.com.cn

The product configuration (including technical parameters) is subject to change and the delivered actual machine without notice.

www.sanyglobal.com