



### **DURABILITY**

- Reliable and high quality. Manufactured by Sany, which is ranked 2nd worldwide and the 1st nationwide in construction machinery industry.
- Stringent testing in Sany's self-built test field. Road test with fully loaded and high intensity for 30,000 km, which is five times more intensive than the one done in Hainan National test field.
- SANY pump truck patented steel technology for chassis and leaf spring(much thicker than competitive products), the bearing performance is improved by 10%.

### **SAFE & COMFORTABLE**

- Equipped with high-end cab, large space, luxury interior, the integration of driving entertainment.
- layout, lower center of gravity that prevents rollovers.

### STRONG POWER

- Weichai power engine, Fast transmission and Hande Axle constitute the golden power train, which contributes to the high climbing performance and low fuel consumption. the climbing performance is improved by 10% and the fuel consumption decreases of 5%
- The Weichai engine is reliable, low maintainance cost and powerful.
- ◆ Fast transmission, standard 2000 N.m torque, higher transmission efficiency, more stable output efficiency.
- The 16T Hande cast steel axles, high ground clearance and excellent trafficability, good waterproof performance, long maintenance period.
- Integrally stamped and formed cabin frame, meet the European certification of positive impact and top pressure inspection.

## **Quality Changes the World**

# **TECHNICAL SPECIFICATIONS**

|                    | Model                                      | SYZ324C-8W(R)                                   |
|--------------------|--|---|
| Overall Parameters | Code                                       | ZZX100000125                                    |
|                    | Rudder Direction                           | Right   |
|                    | Gross Weight(kg)                           | 16200   |
|                    | Full Load Weight(kg)                       | 55000   |
|                    | Dimension (L×W×H)(mm)                      | 8755×2540×3540                                  |
|                    | Wheel Base(mm)                             | 3800+1400                                       |
|                    | Frame(mm)                                  | 860×316×(8+8)                                   |
|                    | Min. Ground Clearance(mm)                  | ≥300  |
|                    | Min. turning diameter(m)                   | ≤22   |
|                    | Braking Distance V <sub>0</sub> =30km/h(m) | ≤10(Full load); ≤9(Empty load)                  |
| Chassis            | Engine                                     | Weichai WP10.380E22                             |
|                    | Displacement(L)                            | 9.726   |
|                    | Rated Power/Rev Speed(kW/rpm)              | 280/2200  |
|                    | Maximum Torgue/Rev Speed(N.m/rpm)          | 1600/1300-1500                                  |
|                    | Emission Standard                          | Euro II   |
|                    | Transmission                               | Fast 12JSD200T-B                                |
|                    | Front Axle(t)                              | 9.5   |
|                    | Middle, Rare Axle(t)                       | 2×16  |
|                    | Cab  | Sany Cab CB318                                  |
|                    | Tyre                                       | 12.00R20  |
|                    | Brake                                      | Pneumatic dual-circuit braking system with drum |
|                    | Fuel Tank(L)                               | 300   |
| Truck              | Cargo Capacity(m³)                         | 24  |
|                    | Cargo Empty(mm)                            | 5800×2300×1800                                  |
|                    | Lifting Angle(°)                           | 45  |
|                    | Lifting Mode                               | Front Lifting                                   |
| Optional           | GPS Terminal-EMEA                          | •   |
| Opti               | ABS  | -   |

