



### **DURABILITY**

- Reliable and high quality. Manufactured by Sany, which is ranked 2nd worldwide and the 1st nationwide in construction machinery industry.
- Stringent testing in Sany's self-built test field. Road test with fully loaded and high intensity for 30,000 km, which is five times more intensive than the one done in Hainan National test field.
- SANY pump truck patented steel technology for chassis and leaf spring(much thicker than competitive products), the bearing performance is improved by 10%, which makes the vehicle suitable for transporting coal mine.

#### **SAFE & COMFORTABLE**

- Equipped with high-end cab, large space, luxury interior, the integration of driving and entertainment.
- Layout, lower center of gravity that prevents rollovers.
- Integrally stamped and formed cabin frame, meet the European certification of positive impact and top pressure inspection.

#### STRONG POWER

- Weichai power engine,Fast transmission and Hande axles constitute the golden power train, which contributes to the high climbing performance and low fuel consumption. the climbing performance is improved by 10% and the fuel consumption decreases of 5%.
- The Weichai engine is reliable, low maintainance cost and powerful.
- ◆ Fast transmission, rated input torque 2400N·m higher transmission efficiency, more stable output efficiency.
- The 16T Hande casting axles have excellent carry performance, waterproof performance and long maintenance interval.

#### **EXCELLENT TRAFFICABILITY**

- The middle and rear axles adopt double reduction axles, the ground clearance is increased by 15% compared with the single reduction axle, which contributes to better trafficability.
- Equipped with inter axle differential lock and inter wheel differential lock, which make the vehicle has strong escape capacity.

## **Quality Changes the World**

# **TECHNICAL SPECIFICATIONS**

	Model	SYZ440C-8W(R)
Overall Parameters	Code	ZZX100000326
	Rudder Direction	Right
	Curb Weight(kg)	20000
	Full Load Weight(kg)	66000
	Dimension (L×W×H)(mm)	11500×2540×3580
	Wheel Base(mm)	2000+4600+1400
	Frame(mm)	860×316×(8+8)
	Min. Ground Clearance(mm)	≥300
	Min. turning diameter(m)	≤26
	Braking Distance V <sub>0</sub> =30km/h(m)	≤10(Full load); ≤9(Empty load)
Chassis	Engine	Weichai WP12.430E201
	Displacement(L)	11.596
	Rated Power/Rev Speed(kW/rpm)	316/1900
	Maximum Torgue/Rev Speed(N.m/rpm)	2000/1000-1400
	Emission Standard	Euro II
	Transmission	Fast 12JSDX240T
	Front Axle(t)	2×9.5
	Middle, Rare Axle(t)	2×16
	Cab	Sany Cab CB318
	Tyre	12.00R20
	Brake	Pneumatic dual- circuit braking system with drum
	Fuel Tank(L)	400
Truck	Cargo Capacity(m³)	40
	Cargo Empty(mm)	8600×2350×2000
	Lifting Angle(°)	45
	Lifting Mode	Front Lifting
Optional	GPS Terminal-EMEA	•
Opt	ABS	-

